



Material Safety Data Sheet

Page:	1 of 3
Issued:	05 02 2009
Revised:	-
Rev. No.:	1
Product:	DRY LUBE

COMPANY DETAILS:

FFS Refiners (Pty) Ltd.
104 Umhlatuzana Road
Sea View, Durban 4094
SOUTH AFRICA

Ph: 031 459 5300
Fax: 031 459 5326
Email: ffs@ffs.co.za

1) PRODUCT DETAILS:

Product name: DRY LUBE
Chemical nature: Liquid Hydrocarbons (C10 - C30)
Synonyms: R50:50
UN no./SIN: 1268

2) COMPOSITION

Liquid Hydrocarbons (C10- C30)

3) HAZARDS IDENTIFICATION

Inflammable (flashpoint approx. 100°C); partially volatile at temperatures in excess of 120°C; can be ignited at temperatures in excess of 100°C if atomised with copious air supply; heating in closed tank can cause pressure rise with risk of bursting or explosion; non-toxic unless ingested in large quantities; mild skin irritant; inhalation of fumes may cause headaches, dizziness and nausea.

4) FIRST AID MEASURES

	Symptom and Effect	First Aid
Skin	Prolonged and repeated contact with skin may cause severe irritation; Toxic if absorbed through the skin; potentially carcinogenic	Wash off with copious quantities of water then with soap and warm water until no odour remains
Eyes	Contact with eyes may cause redness, tearing, blurred vision and moderate irritation.	Flush eyes with clean water for 15 minutes. Seek medical advice if irritation persists.
Ingestion	Harmful or fatal if swallowed. Ingestion of this product may cause central nervous system effects.	If victim is alert, give large amounts of water to drink and seek medical advice. Small amounts can be washed from mouth until no taste remains.
Inhalation	Excessive exposure may cause respiratory tract irritation. Repeated prolonged exposure to high concentrations may lead to central nervous system effects, headaches, dizziness and loss of co-ordination.	Immediately remove to fresh air. Give oxygen if required. Seek medical advice if required.

5) FIRE FIGHTING MEASURES

SMALL FIRES: Use CO₂, foam or dry chemical.

LARGE FIRES: Use CO₂, fluoro protein foam or dry chemicals to extinguish the fire. Use water to cool fire-exposed containers/ structures and to protect personnel. Combustion may release toxic chemicals; utilise respirators; avoid low lying areas.



Material Safety Data Sheet

Page:	2 of 3
Issued:	05 02 2009
Revised:	-
Rev. No.:	1
Product:	DRY LUBE

6) ACCIDENTAL RELEASE MEASURES

Full protective clothing, rubber gloves (PVC, Neoprene, Nitrile, or Viton), gumboots and respirator to be worn. Shut off leaks. Remove all sources of heat or flame. Control spill by use of booms, sand, sawdust or any other suitable available medium. Recover as much free product as possible using pumps or mechanical means. Absorb residue with sawdust, sand or other absorbent material. Avoid the product entering storm water drains or waterways.

7) HANDLING AND STORAGE

Separation of at least 3m from the following classes: Flammable Liquids; Flammable Solids; Spontaneously Combustibles; Poison.
Fire separation of at least 5m from the following classes: Flammable Gases, Oxidising Agents; Organic Peroxides.
Storage in the vicinity of the following classes is prohibited: Explosives, Radio-actives.
Store in accordance with SANS 10089:2003 or SANS 0131:2004 Code of Practice

8) EXPOSURE CONTROLS/ PERSONAL PROTECTION

Occupational Exposure Limits: OHSA 16 mg/m³ TWA OEL-CL
Controls: Store in accordance with SANS 10089:2003-1 or SANS 10131:2004
Personal Protection: Ensure adequate tank ventilation
If engineering controls and work practices are not effective in controlling this material, then wear suitable personal protection equipment including overalls, impervious gloves, respirators, safety goggles, safety boots or gumboots.

9) PHYSICAL AND CHEMICAL PROPERTIES

Brown/ black liquid with paraffin odour. Immiscible with water.
Specific Gravity: 0.88 to 0.96
Flashpoint: >65°C
Boiling Point: >150°C
Viscosity (cSt): 10 @ 100°C

10) STABILITY AND REACTIVITY

Partially volatile at temperatures in excess of 100°C; can be ignited at temperatures in excess of 100°C or if atomised with copious air supply.

11) TOXICOLOGICAL INFORMATION

Some components of the product are suspected carcinogens. Potential harmful effects to liver, kidneys, heart, lungs and nervous system may result from chronic over exposure. Some of the components of the product have been associated with immunological, reproductive, fetotoxic and genotoxic effects.



Material Safety Data Sheet

Page:	3 of 3
Issued:	05 02 2009
Revised:	-
Rev. No.:	1
Product:	DRY LUBE

12) ECOLOGICAL INFORMATION

No ecological problems are expected if the product is handled and used with due care. When released to the environment, some evaporation and bio-degradation will occur. Some components of the product are soluble in water and may contaminate groundwater reserves. Some components of the product will persist in soil. Material is moderately toxic to aquatic organisms.

13) DISPOSAL CONSIDERATIONS

Do not flush to drain/ storm sewer. Product must be disposed of in an approved hazardous waste disposal site or an approved incinerator.
At sea, used or unwanted product should be stored for eventual discharge into port-approved waste oil disposal facilities.

14) TRANSPORT INFORMATION

UN no./SIN	1268
ICS:	Class 3: Group III
IMDG Code:	Class 3
Marine Pollutant:	Yes

15) REGULATORY INFORMATION

National Legislation	National Road Traffic Act 93 of 1996 Hazardous Substances Act 15 of 1973 Occupational Health and Safety Act 85 of 1993 Hazardous Chemical Substances Regulation GNR 1179
----------------------	---

16) OTHER INFORMATION

For more information please contact FFS Refiners' Customer Services Department on (031) 459 5300

THE INFORMATION CONTAINED HEREIN, WHILST APPROPRIATE, IS GENERAL IN NATURE. The information contained herein is also an amalgamation of Good Laboratory Practice-accredited (GLP), in-house derived as well as from published and industry published data. The data is presented in good faith and is to the best of FFS Refiners (Pty) Ltd's knowledge true and accurate. It is presented for information purposes only and without any warranty whatsoever. Due to the special nature of the product and its applications, FFS Refiners (Pty) Ltd does not accept any responsibility or liability whatsoever (including patent infringement) which may result from the use of this information. If in doubt please contact FFS Refiners (Pty) Ltd.

The information contained herein is not to be construed as any licence to operate under, or a recommendation to infringe any existing patents, nor should it be seen as taking preference over any Governmental or international safety codes or regulations.