



Material Safety Data Sheet

Page:	1 of 3
Issued:	22 10 2004
Revised:	14 06 2008
Rev. No.:	5
Product:	WP

COMPANY DETAILS:		
FFS Refiners (Pty) Ltd. 104 Umhlatuzana Road Sea View, Durban 4094 SOUTH AFRICA		Ph: 031 459 5300 Fax: 031 459 5326 Email: ffs@ffs.co.za
1) PRODUCT DETAILS:		
Product name:	Wood Preservative 1, 2 and 3	
Chemical nature:	Creosotes, products of coal coking distillates and petroleum based oils.	
Synonyms:	Coal Tar Fuel, CTF, Recovered Tar, Creosote, wood preservative, coal tar distillate, coking liquid, Coal distillates	
UN No./SIN:	2810 TOXIC LIQUID, ORGANIC, NOS (Creosote)	
2) COMPOSITION		
Substance	(g/l)	Risk Phrase
Creosotes	700-850	Probable carcinogenic, harmful, flammable, toxic
Aromatic oils	100 -200	
Waxy oils	100-200	
Phenolic content	50-150	
3) HAZARDS IDENTIFICATION		
Inflammable liquid (flashpoint greater than 90 ⁰ C); may be harmful if inhaled; harmful if swallowed or if absorbed through skin; contains probable carcinogen compounds.		
4) FIRST AID MEASURES		
	Symptom and Effect	First Aid
Skin	Prolonged and repeated contact with skin may cause severe irritation; Toxic if absorbed through skin; potentially carcinogenic	Wash with soap and water until no odour remains.
Eyes	Very Hazardous in case of eye contact, may cause redness, tearing, blurred vision and irritation.	Flush eyes with clean water for 15 minutes. Seek medical advice if irritation persists.
Ingestion	Harmful or fatal if swallowed. Ingestion of this product may cause central nervous system effects.	If victim is alert, give large amounts of water to drink and seek medical advice. Small amounts can be washed from mouth until no taste remains.
Inhalation	Excessive exposure may cause respiratory tract irritation. Repeated prolonged exposure to high concentrations may lead to central nervous system effects, headaches, dizziness and loss of co-ordination.	Immediately remove to fresh air. Give oxygen if required. Seek medical advice if required.
5) FIRE FIGHTING MEASURES		
SMALL FIRES: Use CO ₂ , foam or dry chemical.		
LARGE FIRES: Use CO ₂ , fluoro protein foam or dry chemicals to extinguish the fire. Use water to cool fire exposed containers/ structures and to protect personnel. Combustion may release toxic chemicals; utilise respirators; avoid low-lying areas.		



Material Safety Data Sheet

Page:	2 of 3
Issued:	22 10 2004
Revised:	14 06 2008
Rev. No.:	5
Product:	WP

6) ACCIDENTAL RELEASE MEASURES	
Full protective clothing, rubber gloves (PVC, Neoprene, Nitrile, or Viton), gumboots and respirator to be worn. Shut off leaks. Remove all sources of heat or flame. Control spill by use of booms, sand, sawdust or any other suitable available medium. Recover as much free product as possible using pumps or mechanical means. Absorb residue with sawdust, sand or other absorbent material. Avoid the product entering storm water drains or waterways.	
7) HANDLING AND STORAGE	
Handling: Full protective clothing should be worn when handling the product. A high standard of personal hygiene is essential. Application of protective hand creams may be beneficial.	
Handling temperature: Avoid extreme temperatures	
Storage: Store away from strong oxidisers. Incompatible with sulphuric acid, nitric acid, caustics, aliphatic amines and amides.	
Storage Conditions: Storage conditions should comply with the relevant SANS Codes. Product should be stored in a well ventilated area. Sparks, flames and other sources of ignition near the product should be avoided. Do not eat, drink or smoke in storage area.	
8) EXPOSURE CONTROLS/ PERSONAL PROTECTION	
Occupational Exposure Limits: Controls: Personal Protection:	NIOSH (US 2002) TWA: 0.1 mg/m ³ Store in accordance with relevant SANS code. Ensure adequate tank ventilation If engineering controls and work practices are not effective in controlling this material, then wear suitable personal protection equipment including overalls, impervious gloves, respirators, safety goggles, safety boots or gumboots.
9) PHYSICAL AND CHEMICAL PROPERTIES	
Black liquid with typical tar/creosote odour. Low solubility in water. Density @ 20°C, kg/l: 1.0 to 1.04 Flashpoint @ 101, 325 kPa: >90°C Boiling Point: 190°C Viscosity (cSt): 4 to 6 @ 90°C	
10) STABILITY AND REACTIVITY	
Partially volatile at temperatures in excess of 90°C; avoid strong oxidisers. Incompatible with sulphuric acid, nitric acid, caustics, aliphatic amines and amides.	
11) TOXICOLOGICAL INFORMATION	
Some components of the product are suspected carcinogens. Potentially harmful effects to liver, kidneys, heart, lungs and nervous system may result from chronic over exposure. Some of the components of the product have been associated with immunological, reproductive, fetotoxic and genotoxic effects.	



Material Safety Data Sheet

Page:	3 of 3
Issued:	22 10 2004
Revised:	14 06 2008
Rev. No.:	5
Product:	WP

12) ECOLOGICAL INFORMATION

No ecological problems are expected if the product is handled and used with due care. When released to the environment, some evaporation and bio-degradation will occur. Some components of the product are soluble in water and may contaminate groundwater reserves. Some components of the product will persist in soil. Material is moderately toxic to aquatic organisms.

13) DISPOSAL CONSIDERATIONS

Do not flush to drain/ storm sewer. Product must be disposed of in an approved hazardous waste disposal site or an approved incinerator.

14) TRANSPORT INFORMATION

UN No./SIN	2810
Hazchem	3W
Class	6.1
IMDG Code:	
Marine Pollutant:	Yes

15) REGULATORY INFORMATION

National Legislation	National Road Traffic Act 93 of 1996 Hazardous Substances Act 15 of 1973 Occupational Health and Safety Act 85 of 1993 Hazardous Chemical Substances Regulation GNR 1179
----------------------	---

16) OTHER INFORMATION

For more information please contact FFS Refiners' Customer Services Department on (031) 459 5300

THE INFORMATION CONTAINED HEREIN, WHILST APPROPRIATE, IS GENERAL IN NATURE. The information contained herein is also an amalgamation of Good Laboratory Practice-accredited (GLP), in-house derived as well as from published and industry published data. The data is presented in good faith and is to the best of FFS Refiners (Pty) Ltd's knowledge true and accurate. It is presented for information purposes only and without any warranty whatsoever. Due to the special nature of the product and its applications, FFS Refiners (Pty) Ltd does not accept any responsibility or liability whatsoever (including patent infringement) which may result from the use of this information. If in doubt please contact FFS Refiners (Pty) Ltd.

The information contained herein is not to be construed as any licence to operate under, or a recommendation to infringe any existing patents, nor should it be seen as taking preference over any Governmental or international safety codes or regulations.